



AMP[®]

Communication Headset

CONNECTORIZED VERSION

3-D Hear-Through and Advanced Hearing Protection in a Mission Configurable Design

Ops-Core headsets are designed to maintain natural hearing and sound localization. Advanced 3D Hear-Through technology and hearing protection capabilities in the Ops-Core AMP Communication Headset further enhance situational awareness and user safety. For optimal flexibility and performance, the modular headset can be easily configured to meet a wide range of mission needs with options for headband or helmet mounted use, single or double hearing protection, single or multi-channel communications, and changeable Camo Skin Sets.



CE 2797
EN352

KEY FEATURES

■ World Class Audio Quality

Leveraging industry-leading military and industrial safety hearing protection and communication systems' capabilities of parent company Gentex Corporation, the Ops-Core AMP Communication Headset provides unprecedented audio quality with the ability to operate in combat environments.

■ 3D Hear-Through (3DHT)

Restores and enhances "natural hearing" of outside environment for improved situational awareness. Ear-simulator design reproduces ambient sounds with a high degree of directional accuracy, while also providing robust hearing protection.

■ Optional NFMI (Near Field Magnetic Induction) Earplugs (sold separately)

Provide increased noise reduction, while maintaining clear communications and 3D Hear-Through ability. NFMI Earplugs do not require wires or batteries. NOTE: Compatible with NFMI-enabled headsets only.

■ Quick-Release Download Connections

Disconnect headset from download(s) to allow for set up on left, right, or both sides. System can quickly configure between single, dual, or no download. Easy to use Push to Talk (PTT) connection permits secure, clear audio transmission in high noise environments.

■ Earseals

Ergonomically designed to fit head geometry, providing better seal and increased noise attenuation.

■ Auto Shut-Down

To preserve battery life, alert tones signal 3DHT shut down after two hours of inactivity. Pressing volume button resets timer. Included AAA lithium batteries provide 120 hours of 3DHT use.

■ Noise-Cancelling Microphone

Mitigates background noise enabling clear communication. Can be mounted to left or right earcup or removed as preferred.

■ Mission Configurable Capability

Dual configuration capability adapts headset to either headband or helmet-mounted preference based on operational requirements.

Ergonomic Headband

Engineered for optimal comfort and streamlined profile; capable of being worn under a helmet. Quick attach/detach from headband capability.

Rail Mount Kit (sold separately)

Optional rail arms can be mounted to the rear of the Ops-Core ARC™ Rails, leaving top portion of rails free for other accessories, while increasing helmet stabilization and providing a counterbalancing effect of shroud mounted devices. Single point gimbal attachment to earcups allows for 360° adjustment, providing a better earseal and accommodation of head movement. Rotate earcups to side or rear of helmet to create low profile, streamlined stowage when not in use.

■ Integrated Microphone Mounting & Connection Point

Enables easy integration with any U-173/U standard plug.

■ Fail-Safe Communications

In the event of battery loss, 3DHT will power off leaving headset and earplugs to operate for standard communication.

■ Camo Skin Sets (sold separately)

To suite your mission, choose from a comprehensive suite of optional Skin Sets available in Tropic, Alpine, Black, and standard MultiCam®.

■ Berry Amendment Compliant and CE Approved

The AMP Communication Headset is Berry Amendment compliant and CE approved EN 352.



AMP Communication Headset

SPECIFICATIONS

Noise Protection Ratings:

| | |
|--|---|
| Headset Alone: | NRR 22 dB SNR 27 dB H 31 dB M 23 dB L 19 dB |
| NFMI Version (when used with optional NFMI Earplugs): | NRR 34 dB SNR 41 dB H 41 dB M 39 dB L 34 dB |

Battery Run Time:

Up to 120 Hrs w/ Lithium Batteries
@ 21°C

Battery Run Time w/ NFMI Engaged :

Up to 80 Hours w/ Lithium Batteries
@ 21°C

Salt Water Immersion:

IPX7

Environmental:

MIL-STD-810G

Operating Temperature:

-40°C to +55°C (-40°F to +131°F)
w/ Lithium Batteries

Storage Temperature:

-40°C to +71°C (-40°F to +160°F)

EMI Testing Standards

MIL-STD-461G

CE Certification





EN352

Weight*:

| | |
|---------------------------------|------------------|
| Headband Configuration | 0.85 lbs (386 g) |
| NFMI Headband Configuration | 0.92 lbs (419g) |
| Rail Mounted Configuration | 0.94 lbs (426g) |
| NFMI Rail Mounted Configuration | 1.01 lbs (460g) |

**Weights calculated with batteries*

Manufacturer Part Number:

| | |
|--|---|
|  Tan 499, Connectorized, NFMI N101153-02-0000 |  Black, Connectorized, NFMI N101153-02-0001 |
| Tan 499, Connectorized N101153-01-0000 | Black, Connectorized N101153-01-0001 |
|  Foliage Green, Connectorized, NFMI N101153-02-0002 |  Urban Gray, Connectorized, NFMI N101153-02-0003 |
| Foliage Green, Connectorized, N101153-01-0002 | Urban Gray, Connectorized N101153-01-0003 |

Contact Us

Designed to seamlessly integrate, our comprehensive suite of modular, scalable, open architecture helmet systems provide today's elite defense, law enforcement, and security forces with true system level performance. For more information on the Ops-Core AMP Communication Headset, contact Ops-Core communication specialists at directly at 888.894.1755 or support@ops-core.com.

Gentex Corporation

645 Harvey Road, Suite 102

Manchester, NH 03103

Tel: 888.894.1755

Fax: 603.657.1201

www.ops-core.com

Copyright 2020 Gentex Corporation. Ops-Core, AMP and the Ops-Core logo are registered trademarks of Gentex Corporation or its affiliates. Ops-Core ARC is a trademark of Gentex Corporation or its affiliates. MultiCam is a registered trademark of LineWeight, LLC. This product is covered by one or more patents. For more information visit www.gentexcorp.com/patents. REV. 20200903