



Technical Data ZEISS DTI 1, DTI 3 GEN 2, DTI 4

Models	DTI 1		DTI 3 GEN 2		DTI 4	
Focal Range in mm / aperture	19/F1.0	25/F1.0	25/F1.0	35/F1.0	35/F1.0	50/F1.1
Resolution sensor in pixel	384 x 288		384 x 288		640 x 512	
Sensor Pitch in mikron	12		17		12	
Frame rate in Hz	50		50		50	
Resolution of display in pixel	1280 x 960		1024 x 768		1024 x 768	
Display type	LCOS		AMOLED		AMOLED	
Range in m	1000m	1320m	930m	1300m	1845m	2635m
Field of view Objective in m at 100m	24m	18m	26m	19m	22m	15m
Field of view lens side in ° (horizontal x vertical)	14° x 10°	10.5° x 8°	15° x 11°	11° x 8°	12.5° x 10°	9° x 7°
Optical magnification	1.8x	2.5x	1.7x	2.4x	2.0x	2.9x
Maximum digital zoom	4x		4x		4x	
Zoom steps	In 0,5x steps: 1.0x – 4.0x		In 0,5x steps: 1.0x – 4.0x		In 0,5x steps: 1.0x – 4.0x	
Interfaces	USB: Charging + Data WLAN: Data		USB: Charging + Data WLAN: Data		USB: Charging + Data WLAN: Data	
Battery type	Li-Ion		Li-Ion		Li-Ion	
Battery run time	6,5h		8h		7h	
External power supply in V	5V/2A		5V/2A		5V/2A	
Internal storage	16GB		32GB		32GB	
Video / Photo / Livestream function	yes		yes		yes	
WLAN Frequency	2.4 GHz		2.4 GHz		2.4 GHz	
WLAN Standard	IEEE 802.11 b/g/n		IEEE 802.11 b/g/n		IEEE 802.11 b/g/n	
Connection to other devices	ZEISS Hunting App or USB		ZEISS Hunting App or USB		ZEISS Hunting App or USB	
IP protection class	IP 65		IP 66		IP 66	
Operating temperature range	-10°C to +50°C		-10°C to +50°C		-10°C to +50°C	
Length*width*height	175mm x 57mm x 62mm	175mm x 57mm x 62mm	187mm x 60mm x 65mm	193mm x 60mm x 65mm	193mm x 60mm x 65mm	206mm x 60mm x 65mm
Weight	360g	360g	410g	420g	430g	470g

Subject to changes in design and scope of delivery, as a result of ongoing technical development.

For further product information visit www.zeiss.com/hunting/thermal-imaging-cameras